

## Differences between WIZ600Wi and WIZ610Wi

|                                | WIZ600Wi                                     | WIZ610Wi  |
|--------------------------------|--|---|
| Frequency Range                | 2.400~2.483GHz                               | 2.412~2.485GHz                                  |
| Output Power                   | 18dBm  | 14dBm   |
| Sensitivity                    | -68dBm@54Mbps                                | -76dBm@54Mbps/11g                               |
| Performance                    | Max.33Mbps Real Data Streaming(@54Mbps)      | Max.25Mbps Effective Data Transmission(@54Mbps) |
| Support Multiple SSID and VLAN | ○  |   |
| Radio Enable/Disable           | ○  |   |
| SSID Hidden                    | ○  | ○   |
| Auto Channel Select            | ○  | ○   |
| TX Power Control               | ○  | Auto  |
| WPA/WPA2                       | ○  | ○   |
| Virtual Server                 | ○  | ○   |
| PPPoE/PPTP                     |  | ○   |
| DMZ                            |  | ○   |
| DDNS                           |  | ○   |
| Logging                        | ○  | ○   |
| MAC filtering                  | ○  | ○   |
| IP filtering                   |  | ○   |
| Packet Filtering               | ○  |   |
| SNMP                           | ○  | soon  |
| Temperature                    | Operation : 0 ~ 55°C<br>Storage : -20 ~ 65°C | Operation : 0 ~ 55°C<br>Storage : -20 ~ 70°C    |
| Through Hole                   | none   | Ø3mm hole X 1                                   |
| Dimension                      | 51mm X 46mm X 7mm                            | 39mm X 32mm X 4.7mm                             |
| Power Consumption              | Max 700mA @ 3.3V                             | Max 800mA @ 3.3V                                |